



BJÖRK Baby Changing Station with safety strap 3220/3222/3224



reddot design award
best of the best



GERMAN
DESIGN
AWARD
WINNER
2018



Wall mounted
Powder coated aluminum
2-year warranty

The BJÖRK baby changing station by DAN DRYER has been awarded several prestigious design prizes. Perfectly adapted ergonomically, it provides a comfortable and secure base for the infant, and with its design approach marked by purism and practical use, it goes far beyond familiar forms by creating a highly refined aesthetic. The baby changing station meets the highest demands, offering a great deal of comfort for both infants and parents. This product is SGS certified, compliant with the American standard ASTM F2285-04 and the European EN 12221-. It also meets ADA regulations when installed according to ADA guidelines.

Application

BJÖRK, a true breakthrough in commercial bathroom products. The elegant design line is suitable for all types of commercial washrooms and public areas.

References

Offices and administration, shopping malls, restaurants, hotels, airports, sports centers, schools, and public institutions.

Technical data

	BJÖRK
	Prod. No.: 3220, 3222, 3224
Type	Baby changing station
Width	552 mm
Depth (folded up)	100 mm
Depth (folded down)	760 mm
Height (folded up)	781 mm
Height (folded down)	304 mm
Changing surface	L 700 mm x W 510 mm
Height of protective sides	55 mm
Dimensions wall plate	400 x 300 x 3 mm
Load capacity	80 kg
Recommended working height	950 mm above floor
Force required to open	~20 N; to close: ~20 N
Net weight	17 kg

Tender text

Baby changing station. Powder coated steel wall unit, powder coated aluminum profile and electro-galvanized steel axle and levers. Load capacity: 80 kg. Net weight: 17 kg. H 781 mm (up)/304 mm (down), W 552 mm, D 100 mm (up)/760 mm (down).

Standard colors

Prod. No. 3220: RAL 9003, white, gloss 75
Prod. No. 3222: RAL 9005, black, gloss 7-12
Prod. No. 3224: RAL Classic colors

Materials

Changing surface: Powder coated aluminium profile.
Wall unit: Powder coated steel plate.
Axle and levers: Electro-galvanized steel.

Installation

Wall mounting. The recommended working height above floor: Approx. 950 mm.

Function

Torsion springs ensure the smooth and easy opening and closing motion of the unit.

Certification

Tested in accordance with DIN EN 12221-1:2008 + A1:2013, and the American standard ASTM F2285-04.