



LOKI Warm-Air Hand Dryer

4000/4002/4004/4006



GERMAN
DESIGN
AWARD
WINNER
2021



reddot winner 2021



High-speed
IR-sensor and electronic timer
5-year warranty

DAN DRYER LOKI high-speed hand dryer; award winning and ADA compliant. Its elegant and functional design is characterised by clean lines and rectangular shapes, which complements the surrounding architecture. The robust front plate with the high light guide maintains the design theme throughout the LOKI range.


Application

DAN DRYER LOKI is a compact, high-speed hand dryer in sleek design. Featuring short drying time and low maintenance, this reliable machine is suitable for all high traffic public and commercial areas.

References

Offices and administration, shopping centres, restaurants, hotels and leisure, airports, schools, and sports facilities.

Technical data

	LOKI Prod. No.: 4000, 4002, 4004, 4006	
Type	Warm-air hand dryer with IR sensor	
Dimensions	H 300 x W 173 X D 102 mm	
Material	Brushed or powder coated stainless steel	
Drying cycle	10-15 sec.	
Connection	230 V, 50/60 Hz, Class I 	
Total wattage	840-1000 W	
Heating element	500 W	
Motor	340-500 W	
Noise level	69-76.6 dB @ 1 m	
Max. air capacity	95-115 m/sec.	
Max. air outlet temperature	55°C	
Net weight	4.5 kg	
IP rating	IP24	

Standard colours

Prod. No. 4000: Brushed stainless steel
Prod. No. 4002: RAL 9003, white, gloss 60
Prod. No. 4004: RAL 9005, matt black, gloss 10
Prod. No. 4006: RAL Classic colours

Activation

Infrared sensor and electronic timer. Touch free. Activation distance adjustable 172 mm (\pm 20 mm). Automatic stop after 60 seconds of continuous use.

Motor type

Commutator motor with carbon brushes. 16,000-29,000 revolutions/min.

Protection

Automatic thermal cut-out in both motor and heating element.

Tender text

Touch-free hand dryer in stainless steel, brushed or powder coated Infra-red sensor and electronic timer, drying cycle: 10-15 sec. IP24, 230 V, 50/60 Hz, 840-1000 W, Class I (earthed), 69-76.6 dB @ 1 m dBA. Net weight: 4.5 kg. H: 300mm, W: 173mm, D: 102mm.

Installation

Machine intended for wall-mounting and fixed installation via circuit-breaker. Installation must be carried out by a qualified electrician.

Compliance:

CE, WEEE, RoHS, UKCA